

Accessories

| | |
|-----------------------------|---|
| Supplied Accessories | Remote control, power cord, computer cable, 2 AA batteries, cable cover, adapter cover, application CD, user's manual |
| Optional Accessories | HAS-WM05 wall mount, wall plates, wall adapter, USBWL11N USB wireless adapter, MS-1 wired and MS-1WL wireless multifunction switchers, TT-03 tabletop stand |
| Replacement Parts | |
| Lamp | DT01511 with filter |
| Remote Control | HL03033 |
| Filter | UX37191 |

Projection Throw Chart (In inches)

| Screen Size 16:10 | | |
|-------------------|-------|----------------|
| Diagonal | Width | Throw Distance |
| 60 | 5.0 | 16.1 |
| 70 | 7.8 | 18.9 |
| 80 | 10.5 | 21.6 |
| 90 | 13.3 | 24.4 |
| 100 | 16.1 | 27.1 |

Throw Ratio: (distance : width)
0.2 : 1 from edge of projector
0.3 : 1 from mirror cover

Specifications

| | | |
|--------------------|---|--|
| Display | Projection Technology | 3LCD, 3 chip technology |
| | Resolution | WXGA 1280 x 800 |
| | White Light Output | 2,700 ANSI lumens |
| | Color Light Output | 2,700 ANSI lumens |
| | Colors | 16.7 million colors |
| | Aspect Ratio | Native 16:10 / 4:3 and 16:9 compatible |
| | Contrast Ratio | 10,000 : 1 (using active IRIS) |
| Lens & Operation | Throw Ratio (distance : width) | 0.2 : 1 from edge of projector to screen 0.3 : 1 from mirror cover to screen |
| | Focus Distance | 16" - 27" from mirror cover to screen |
| | Display Size | 60" - 100" |
| | Lens | f = 4.21 mm |
| | Lamp Wattage | 225W |
| | Expected Lamp Life* | Approximately 5,000 hours (standard mode) 10,000 hours (Eco-2 mode) |
| | Expected Filter Life** | Approximately 4,000 hours |
| Compatibility | Speaker Output | 16W x 1 |
| | Keystone | H and V: +/- 5° |
| | Computer | VGA, SVGA, XGA, WXGA/WXGA+/SXGA/SXGA+/UXGA (compressed), MAC 16" |
| | H-Sync | 15 kHz - 106 kHz |
| | V-Sync | 50 Hz - 120 Hz |
| | Composite Video | NTSC, NTSC4.43, PAL, PAL-M, -N, SECAM |
| | Component Video | 480i, 480p, 576i, 720p, 1080i, 1080p |
| Connectors | HDMI | 480i, 480p, 576i, 720p, 1080i, 1080p, computer signal TMDS clock 27 MHz - 150 MHz |
| | Digital Input | HDMI x 2 (HDCP compliant) |
| | Computer Input 1 | 15-pin mini D-sub x 1 |
| | Computer Input 2 | 15-pin mini D-sub x 1 |
| | Computer Monitor Output | 15-pin mini D-sub x 1 |
| | Video Input | |
| | S-Video | N/A |
| | Composite Video | RCA jack x 1 |
| | Component Video | 15-pin mini D-sub x 2 (shared with computer in 1/2) |
| | Audio Input | 3.5 mm stereo mini jack x 1, RCA jack (L/R) x 1, MIC-in 3.5 mm mini jack x 1 |
| | Audio Output | 3.5 mm stereo mini jack x 1 |
| | Network LAN Wired | RJ-45 port (10 base-T / 100 base-TX) |
| | Network LAN Wireless | USB-A, IEEE802.11 b/g/n - optional wireless adapter required |
| Ratings & Warranty | USB | Type A x 2 (PC-less presentation, wireless adapter) Type B x 1 (USB display or mouse control) |
| | Control Terminals | 9-pin D-sub x 1 (RS-232 control) |
| | Power Supply | AC90-132V / AC198-264V, 50/60Hz |
| | Power Consumption | 330W |
| | Operating Temperature | 32°F - 104°F (0°C - 40°C) |
| | Dimensions (W x D x H) | 14.8" x 14.2" x 5.4" (excluding protruding parts) |
| | Weight | Approximately 9.4 lbs |
| Approvals | UL 60950-1 / cUL, FCC part 15 subpart B Class B | |
| Warranty | 3 year limited parts and labor Extended Service Contract available (additional cost) | |

* Actual lamp life will vary by individual lamp based on environmental conditions, selected operating mode, user settings and usage. Hours of average lamp life specified are not guaranteed and do not constitute part of the product or lamp warranty. Lamp brightness decreases over time.

** Actual filter life will vary by individual filter based on environmental conditions, selected operating mode, user settings and usage. Hours of average filter life specified are not guaranteed and do not constitute part of the product warranty.



HI0389-Rev.3-11/16

All specifications subject to change without notice.

3LCD and the 3LCD logo are registered trademarks of the Seiko Epson Corporation.
©2016 Hitachi America, Ltd. All Rights Reserved.

Hitachi America, Ltd.

Toll Free: 1.800.HITACHI • Email: dmd.info@hal.hitachi.com
Web: hitachi-america.us/projectors



HDMI

