



Accessories	
<b>Supplied Accessories</b>	Remote control, power cord, computer cable, lithium battery x 1, user's manual CD, user's manual
<b>Optional Accessories</b>	N/A
Replacement Parts	
<b>Lamp</b>	DT01853
<b>Remote Control</b>	HL02961

Projection Throw Chart (In inches)

Screen Size 4:3		Throw Distance	
Diagonal	Width	Min	Max
60	48	94	103
70	56	110	120
80	64	125	138
90	72	141	155
100	80	156	172
120	96	188	207
150	120	235	258
200	160	313	344
250	200	391	430

Throw Ratio: (distance : width)  
1.96 - 2.15 : 1

## Specifications

Display	<b>Projection Technology</b>	Single chip DLP
	<b>Resolution</b>	XGA 1024 x 768
	<b>Brightness</b>	3,500 ANSI lumens
	<b>Colors</b>	1.07 billion colors
	<b>Aspect Ratio</b>	Native 4:3 / 16:9 compatible
	<b>Contrast Ratio</b>	10,000:1
	<b>Throw Ratio (distance : width)</b>	1.96 - 2.15 : 1
Lens & Operation	<b>Focus Distance</b>	94" - 310"
	<b>Display Size</b>	60" - 250"
	<b>Lens</b>	f = 22 - 24.1 mm
	<b>Lamp Wattage</b>	220W
	<b>Expected Lamp Life*</b>	Approximately 3,500 hours (standard mode) 5,000 hours (Eco mode)
	<b>Expected Filter Life</b>	N/A
	<b>Speaker Output</b>	2W x 1
Compatibility	<b>Keystone</b>	+/- 30° vertical only
	<b>Computer</b>	VGA, SVGA, XGA, WXGA/WXGA+/SXGA/SXGA+/WSXGA+/UXGA/WUXGA (compressed), MAC 16"
	<b>H-Sync</b>	31.5 kHz - 102 kHz
	<b>V-Sync</b>	59.9 Hz - 120 Hz
	<b>Composite Video</b>	NTSC, NTSC4.43, PAL, PAL-M, -N, SECAM
	<b>Component Video</b>	480i, 480p, 576i, 576p, 720p, 1080i, 1080p
	<b>HDMI</b>	480i, 480p, 576i, 576p, 720p, 1080i, 1080p
Connectors	<b>Digital Input</b>	HDMI x 1 (HDCP compliant)
	<b>Computer Input 1</b>	15-pin mini D-sub x 1
	<b>Computer Input 2</b>	15-pin mini D-sub x 1
	<b>Computer Monitor Output</b>	15-pin mini D-sub x 1
	<b>Video Input</b>	
	S-Video	Mini DIN 4-pin x 1
	Composite Video	RCA jack x 1
	Component Video	15-pin mini D-sub x 2 (shared with computer in 1/2)
	<b>Audio Input</b>	3.5 mm stereo mini jack x 1
	<b>Audio Output</b>	3.5 mm stereo mini jack x 1
	<b>Network LAN Wired</b>	N/A
<b>Network LAN Wireless</b>	N/A	
Ratings & Warranty	<b>USB</b>	Type B x 1 (firmware update)
	<b>Control Terminals</b>	9-pin D-sub x 1 (RS-232 control)
	<b>Power Supply</b>	AC100-120V / AC220-240V, 50/60Hz
	<b>Power Consumption</b>	290W
	<b>Operating Temperature</b>	32°F - 95°F (0°C - 35°C)
	<b>Dimensions (W x D x H)</b>	12.4" x 8.2" x 3.5" (excluding protruding parts)
	<b>Weight</b>	Approximately 5.1 lbs.
	<b>Approvals</b>	UL 60950-1 / cUL FCC Part 15 subpart B class B
	<b>Warranty</b>	3 year limited parts and labor. Extended Service Contract available (additional cost)

\* Actual lamp life will vary by individual lamp based on environmental conditions, selected operating mode, user settings and usage. Hours of average lamp life specified are not guaranteed and do not constitute part of the product or lamp warranty. Lamp brightness decreases over time.



HDMI



Trade-Up Program

# CP-DX351

