

## Accessories and Lenses

<b>Supplied Accessories</b>	Remote control, power cord, computer cable, AA batteries x 2, security label, user's manual (concise)
<b>Optional Accessories</b>	N/A
<b>Optional Lenses</b>	NA
<b>Replacement Parts</b>	
<b>Lamp</b>	DT02081
<b>Remote Control</b>	HL03037
<b>Filter</b>	UX39561

## Projection Throw Chart

Screen Size 16:10		Throw Distance	
Diagonal	Width	Min	Max
30	24	33	40
60	48	69	83
80	64	93	112
100	80	116	140
200	160	236	284
300	240	355	427

Throw Ratio: 1.5 - 1.8 : 1 (distance : width)  
Screen size and throw distance are measured in inches.

## Specifications

Display	<b>Projection Technology</b>	3LCD, 3 chip technology
	<b>Resolution</b>	XGA - 1024 x 768
	<b>White Light Output</b>	3,300 ANSI lumens
	<b>Color Light Output</b>	3,300 ANSI lumens
	<b>Colors</b>	16.7 million colors
	<b>Aspect Ratio</b>	Native 4:3 and 16:9 / 16:10 / 14:9 zoom compatible
	<b>Contrast Ratio</b>	20,000 : 1 (using active IRIS)
Lens & Operation	<b>Throw Ratio</b> (distance : width)	1.5 - 1.8 : 1
	<b>Focus Distance</b>	33" - 427"
	<b>Display Size</b>	30" - 300"
	<b>Lens</b>	f = 19 - 23 mm, x 1.2 manual zoom and focus
	<b>Lamp Wattage</b>	230W
	<b>Expected Lamp Life*</b>	Approximately 6,000 hours (standard mode) 12,500 hours (eco mode)
	<b>Expected Filter Life**</b>	Approximately 10,000 hours
Compatibility	<b>Speaker Output</b>	1W
	<b>Keystone</b>	V: +/- 30°
	<b>Computer</b>	VGA, SVGA, XGA, WXGA/SXGA/SXGA+/HD/UXGA (compressed), Mac 16"
	<b>H-Sync</b>	15 kHz - 106 kHz
	<b>V-Sync</b>	50 Hz - 120 Hz
	<b>Composite Video</b>	NTSC, NTSC4.43, PAL, PAL-M, -N, SECAM
	<b>Component Video</b>	480i, 480p, 576i, 576p, 720p, 1080i, 1080p
Connectors	<b>HDMI</b>	480i, 480p, 576i, 576p, 720p, 1080i, 1080p Computer signal TMDS Clock 25 MHz - 162 MHz
	<b>Digital Input</b>	HDMI x 1 (HDCP compliant)
	<b>Computer Input 1</b>	15-pin mini D-sub x 1 (shared with analog component video input)
	<b>Computer Input 2</b>	15-pin mini D-sub x 1 (shared with analog component video input and monitor out)
	<b>Computer Monitor Output</b>	15-pin mini D-sub x 1 (shared with computer in 2 and analog component video input 2)
	<b>Video Input</b>	
	<b>Audio Input</b>	RCA jack (L/R) x 1
Ratings & Warranty	<b>Audio Output</b>	3.5mm stereo mini jack x 1
	<b>Network LAN Wired</b>	N/A
	<b>Network LAN Wireless</b>	N/A
	<b>USB</b>	N/A
	<b>Control Terminals</b>	9-pin D-sub x 1 (RS-232 control)
	<b>Power Supply</b>	AC100-120V / AC220-240V, 50/60Hz
	<b>Power Consumption</b>	290W / 280W
<b>Operating Temperature</b>	32°F - 95°F (0°C - 35°C)	
<b>Dimensions (W x D x H)</b>	13.7" x 10.4" x 3.5" (excluding protrusions)	
<b>Weight</b>	Approximately 7.7 lbs.	
<b>Approvals</b>	UL 60950-1 / cUL FCC Part 15 subpart B class B	
<b>Warranty</b>	3 years limited parts and labor Extended Service Contract available (additional cost)	

\* Actual lamp life will vary by individual lamp based on environmental conditions, selected operating mode, user settings and usage. Hours of average lamp life specified are not guaranteed and do not constitute part of the product or lamp warranty. Lamp brightness decreases over time.

\*\* Actual filter life will vary by individual filter based on environmental conditions, selected operating mode, user settings and usage. Hours of average filter life specified are not guaranteed and do not constitute part of the product.

HI0615-08/18

All specifications subject to change without notice.

3LCD and the 3LCD logo are registered trademarks of the Seiko Epson Corporation.  
©2018 Hitachi America, Ltd. All Rights Reserved.



## Hitachi America, Ltd.

Toll Free: 1.800.HITACHI • Email: [dmd.info@hal.hitachi.com](mailto:dmd.info@hal.hitachi.com)  
Web: [hitachi-america.us/projectors](http://hitachi-america.us/projectors)

