



Ultra Short Throw models



CP-D32WN



CP-DX300

	ULTRA SHORT THROW				SHORT THROW	DLP®
	CP-AX2503	CP-AX3503	CP-AW2503	CP-AW3003	CP-D32WN	CP-DX300
<b>Projector Technology</b>	3LCD, 3 chip technology	3LCD, 3 chip technology	3LCD, 3 chip technology	3LCD, 3 chip technology	3LCD, 3 chip technology	Single chip DLP
<b>Resolution</b>	XGA 1024 x 768	XGA 1024 x 768	WXGA 1280 x 800	WXGA 1280 x 800	XGA 1024 x 768	XGA 1024 x 768
<b>Light Output</b>	2,700 ANSI lumens	3,600 ANSI lumens	2,700 ANSI lumens	3,300 ANSI lumens	3,200 ANSI lumens	3,000 ANSI lumens
<b>Contrast Ratio</b>	5000 : 1 (using active IRIS)	5000 : 1 (using active IRIS)	5000 : 1 (using active IRIS)	5000 : 1 (using active IRIS)	3000 : 1 (using active IRIS)	2500 : 1
<b>Throw Ratio (Distance : width)</b>	0.3 : 1	0.3 : 1	0.3 : 1	0.3 : 1	0.4 : 1	1.86 - 2.04 : 1
<b>Focus Distance</b>	15" - 26" (from mirror cover to screen)	15" - 26" (from mirror cover to screen)	16" - 27" (from mirror cover to screen)	16" - 27" (from mirror cover to screen)	20" - 36"	39" - 472"
<b>Display Size</b>	60" - 100"	60" - 100"	60" - 100"	60" - 100"	60" - 100"	30" - 300"
<b>Expected Lamp Life<sup>1</sup></b>	Approx. 3,000 hours (standard mode); 5,000 hours (Eco mode)	Approx. 2,500 hours (standard mode); 4,000 hours (Eco mode)	Approx. 2,500 hours (standard mode); 4,000 hours (Eco mode)	Approx. 2,500 hours (standard mode); 4,000 hours (Eco mode)	Approx. 3,000 hours (standard mode); 5,000 hours (Eco mode)	Approx. 4,500 hours (standard mode); 6,000 hours (Eco mode)
<b>Expected Filter Life<sup>2</sup></b>	Approx. 4,000 hours	Approx. 4,000 hours	Approx. 4,000 hours	Approx. 4,000 hours	Approx. 4,000 hours	N/A
<b>Speaker Output</b>	16W	16W	16W	16W	10W	2W
<b>Digital Input</b>	HDMI x 2 (HDCP compliant)	HDMI x 2 (HDCP compliant)	HDMI x 2 (HDCP compliant)	HDMI x 2 (HDCP compliant)	HDMI x 1 (HDCP compliant)	HDMI x 1 (HDCP compliant)
<b>Network (LAN) Wired</b>	RJ-45 port (10 base-T / 100 base-TX)	RJ-45 port (10 base-T / 100 base-TX)	RJ-45 port (10 base-T / 100 base-TX)	RJ-45 port (10 base-T / 100 base-TX)	RJ-45 port (10 base-T / 100 base-TX)	N/A
<b>Network (LAN) Wireless</b>	USB-A, IEEE802.11 b/g/n - optional wireless adapter required	USB-A, IEEE802.11 b/g/n - optional wireless adapter required	USB-A, IEEE802.11 b/g/n - optional wireless adapter required	USB-A, IEEE802.11 b/g/n - optional wireless adapter required	USB-A, IEEE802.11 b/g/n - optional wireless adapter required	N/A
<b>Weight</b>	Approx. 9.5 lbs.	Approx. 9.5 lbs.	Approx. 9.5 lbs.	Approx. 9.5 lbs.	Approx. 8.2 lbs.	Approx. 4.8 lbs.
<b>Supplied Accessories</b>	Remote control, power cord, computer cable, user's manual, network manual	Remote control, power cord, computer cable, user's manual, network manual	Remote control, power cord, computer cable, user's manual, network manual	Remote control, power cord, computer cable, user's manual, network manual	Remote control, power cord, computer cable, user's manual, network manual	Remote control, power cord, computer cable, user's manual
<b>Optional Accessories</b>	HAS-WM03 wall mount, wall plates, wall adapter, USBWL11N USB wireless adapter, MS-1 wired and MS-1WL wireless multifunction switchers, TT-03 table top stand	HAS-WM03 wall mount, wall plates, wall adapter, USBWL11N USB wireless adapter, MS-1 wired and MS-1WL wireless multifunction switchers, TT-03 table top stand	HAS-WM03 wall mount, wall plates, wall adapter, USBWL11N USB wireless adapter, MS-1 wired and MS-1WL wireless multifunction switchers, TT-03 table top stand	HAS-WM03 wall mount, wall plates, wall adapter, USBWL11N USB wireless adapter, MS-1 wired and MS-1WL wireless multifunction switchers, TT-03 table top stand	USBWL11N USB wireless adapter, MS-1 wired and MS-1WL wireless multifunction switchers <sup>3</sup>	MS-1 wired and MS-1WL wireless multi-function switchers <sup>3</sup> , LCDSCM2B soft sided case
<b>Optional Lenses</b>	N/A	N/A	N/A	N/A	N/A	N/A
<b>Lamp</b>	DT01511 with filter	DT01411 with filter	DT01411 with filter	DT01411 with filter	DT01381	DT01461
<b>Remote Control</b>	HLO3033	HLO3033	HLO3033	HLO3033	HLO2881	HLO2961
<b>Filter</b>	UX37191	UX37191	UX37191	UX37191	UX37191	N/A

<sup>1</sup> Actual lamp life will vary by individual lamp and based on environmental conditions, selected operating mode, user settings and usage. Hours of average lamp life specified are not guaranteed and do not constitute part of the product or lamp warranty. Lamp brightness decreases over time.

<sup>2</sup> Actual filter life will vary by individual filter and based on environmental conditions, selected operating mode, user settings and usage. Hours of average filter life specified are not guaranteed and do not constitute part of the product warranty.

<sup>3</sup> Switchers have limited function with this projector model

For sales information, please call  
**800.HITACHI**

For complete specifications visit  
**hitachi-america.us/projectors**

Visit our blog  
**dmd.hitachi-america.us/blog**



Interactive models



Classroom/Conference Room models

	INTERACTIVE		CLASSROOM/CONFERENCE ROOM						
	CP-TW2503	CP-TW3003	CP-EX250N	CP-X2530WN	CP-X3030WN	CP-X4030WN	CP-EW300N	CP-WX3030WN	CP-WX3530WN
<b>Projector Technology</b>	3LCD, 3 chip technology	3LCD, 3 chip technology	3LCD, 3 chip technology	3LCD, 3 chip technology	3LCD, 3 chip technology	3LCD, 3 chip technology	3LCD, 3 chip technology	3LCD, 3 chip technology	3LCD, 3 chip technology
<b>Resolution</b>	WXGA 1280 x 800	WXGA 1280 x 800	XGA 1024 x 768	XGA 1024 x 768	XGA 1024 x 768	XGA 1024 x 768	WXGA 1280 x 800	WXGA 1280 x 800	WXGA 1280 x 800
<b>Light Output</b>	2,700 ANSI lumens	3,300 ANSI lumens	2,700 ANSI lumens	2,700 ANSI lumens	3,200 ANSI lumens	4,200 ANSI lumens	3,000 ANSI lumens	3,000 ANSI lumens	3,700 ANSI lumens
<b>Contrast Ratio</b>	5000 : 1 (using active IRIS)	5000 : 1 (using active IRIS)	2000 : 1	4000 : 1 (using active IRIS)	4000 : 1 (using active IRIS)	5000 : 1 (using active IRIS)	2000 : 1	4000 : 1 (using active IRIS)	5000 : 1 (using active IRIS)
<b>Throw Ratio (Distance : width)</b>	0.3 : 1	0.3 : 1	1.5 - 1.8 : 1	1.5 - 1.8 : 1	1.5 - 1.8 : 1	1.5 - 1.8 : 1	1.5 - 1.8 : 1	1.5 - 1.8 : 1	1.5 - 1.8 : 1
<b>Focus Distance</b>	16" - 27" (from mirror cover to screen)	16" - 27" (from mirror cover to screen)	34" - 428"	34" - 428"	34" - 428"	34" - 429"	36" - 454"	36" - 454"	36" - 455"
<b>Display Size</b>	60" - 100"	60" - 100"	30" - 300"	30" - 300"	30" - 300"	30" - 300"	30" - 300"	30" - 300"	30" - 300"
<b>Expected Lamp Life<sup>1</sup></b>	Approx. 2,500 hours (standard mode); 4,000 hours (Eco mode)	Approx. 2,500 hours (standard mode); 4,000 hours (Eco mode)	Approx. 5,000 hours (standard mode); 6,000 hours (Eco mode)	Approx. 5,000 hours (standard mode); 6,000 hours (Eco mode)	Approx. 5,000 hours (standard mode); 6,000 hours (Eco mode)	Approx. 5,000 hours (standard mode); 6,000 hours (Eco mode)	Approx. 4,000 hours (standard mode); 6,000 hours (Eco mode)	Approx. 5,000 hours (standard mode); 6,000 hours (Eco mode)	Approx. 5,000 hours (standard mode); 6,000 hours (Eco mode)
<b>Expected Filter Life<sup>2</sup></b>	Approx. 4,000 hours	Approx. 4,000 hours	Approx. 2,000 hours	Approx. 5,000 hours	Approx. 5,000 hours	Approx. 5,000 hours	Approx. 2,000 hours	Approx. 5,000 hours	Approx. 5,000 hours
<b>Speaker Output</b>	16W	16W	16W	16W	16W	16W	16W	16W	16W
<b>Digital Input</b>	HDMI x 2 (HDCP compliant)	HDMI x 2 (HDCP compliant)	HDMI x 1 (HDCP compliant)	HDMI x 1 (HDCP compliant)	HDMI x 1 (HDCP compliant)	HDMI x 1 (HDCP compliant)	HDMI x 1 (HDCP compliant)	HDMI x 1 (HDCP compliant)	HDMI x 1 (HDCP compliant)
<b>Network (LAN) Wired</b>	RJ-45 port (10 base-T / 100 base-TX)	RJ-45 port (10 base-T / 100 base-TX)	RJ-45 port (10 base-T / 100 base-TX)	RJ-45 port (10 base-T / 100 base-TX)	RJ-45 port (10 base-T / 100 base-TX)	RJ-45 port (10 base-T / 100 base-TX)	RJ-45 port (10 base-T / 100 base-TX)	RJ-45 port (10 base-T / 100 base-TX)	RJ-45 port (10 base-T / 100 base-TX)
<b>Network (LAN) Wireless</b>	USB-A, IEEE802.11 b/g/n - optional wireless adapter required	USB-A, IEEE802.11 b/g/n - optional wireless adapter required	N/A	USB-A, IEEE802.11 b/g/n - optional wireless adapter required	USB-A, IEEE802.11 b/g/n - optional wireless adapter required	USB-A, IEEE802.11 b/g/n - optional wireless adapter required	N/A	USB-A, IEEE802.11 b/g/n - optional wireless adapter required	USB-A, IEEE802.11 b/g/n - optional wireless adapter required
<b>Weight</b>	Approx. 9.9 lbs.	Approx. 9.9 lbs.	Approx. 6.4 lbs.	Approx. 6.8 lbs.	Approx. 6.8 lbs.	Approx. 6.8 lbs.	Approx. 6.8 lbs.	Approx. 6.8 lbs.	Approx. 6.8 lbs.
<b>Supplied Accessories</b>	Remote control, power cord, computer cable, USB cable, interactive software DVD, interactive pen x 2, pen tips x 4, user's manual	Remote control, power cord, computer cable, USB cable, interactive software DVD, interactive pen x 2, pen tips x 4, user's manual	Remote control, power cord, computer cable, user's manual	Remote control, power cord, computer cable, user's manual, security label, application CD, adapter cover	Remote control, power cord, computer cable, user's manual, security label, application CD, adapter cover	Remote control, power cord, computer cable, user's manual, security label, application CD, adapter cover	Remote control, power cord, computer cable, user's manual	Remote control, power cord, computer cable, user's manual, security label, application CD, adapter cover	Remote control, power cord, computer cable, user's manual, security label, application CD, adapter cover
<b>Optional Accessories</b>	HAS-WM03 wall mount, wall plates, wall adapter, USBWL11N USB wireless adapter, MS-1 wired and MS-1WL wireless multifunction switchers, finger touch unit, TT-03 table top mount	HAS-WM03 wall mount, wall plates, wall adapter, USBWL11N USB wireless adapter, MS-1 wired and MS-1WL wireless multifunction switchers, finger touch unit, TT-03 table top mount	MS-1 wired and MS-1WL wireless multifunction switchers, LCDSC2000 soft sided case	USBWL11N USB wireless adapter, MS-1 wired and MS-1WL wireless multifunction switchers, LCDSC2000 soft sided case	USBWL11N USB wireless adapter, MS-1 wired and MS-1WL wireless multifunction switchers, LCDSC2000 soft sided case	USBWL11N USB wireless adapter, LCDSC2000 soft sided case	MS-1 wired and MS-1WL wireless multifunction switchers, LCDSC2000 soft sided case	USBWL11N USB wireless adapter, MS-1 wired and MS-1WL wireless multifunction switchers, LCDSC2000 soft sided case	USBWL11N USB wireless adapter, LCDSC2000 soft sided case
<b>Optional Lenses</b>	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
<b>Lamp</b>	DT01411 with filter	DT01411 with filter	DT01433 with filter	DT01431with filter	DT01431with filter	DT01481 with filter	DT01491 with filter	DT01481 with filter	DT01481 with filter
<b>Remote Control</b>	HL03033	HL03033	HL03031	HL03031	HL03031	HL03031	HL03031	HL03031	HL03031
<b>Filter</b>	UX37191	UX37191	UX38851	UX38841	UX38841	UX38841	UX38851	UX38841	UX38841

<sup>1</sup> Actual lamp life will vary by individual lamp and based on environmental conditions, selected operating mode, user settings and usage. Hours of average lamp life specified are not guaranteed and do not constitute part of the product or lamp warranty. Lamp brightness decreases over time.

<sup>2</sup> Actual filter life will vary by individual filter and based on environmental conditions, selected operating mode, user settings and usage. Hours of average filter life specified are not guaranteed and do not constitute part of the product warranty.

<sup>3</sup> Switchers have limited function with this projector model

For sales information, please call  
**800.HITACHI**

For complete specifications visit  
**hitachi-america.us/projectors**

Visit our blog  
**dmd.hitachi-america.us/blog**



Collegiate models



Installation models

	COLLEGIATE			INSTALLATION		
	CP-X5022WN	CP-WX4022WN	CP-X8160	CP-WX8255A	CP-WU8440	CP-WU8450
<b>Projector Technology</b>	3LCD, 3 chip technology	3LCD, 3 chip technology	3LCD, 3 chip technology	3LCD, 3 chip technology	3LCD, 3 chip technology	3LCD, 3 chip technology
<b>Resolution</b>	XGA 1024 x 768	WXGA 1280 x 800	XGA 1024 x 768	WXGA 1280 x 800	WUXGA 1920 x 1200	WUXGA 1920 x 1200
<b>Light Output</b>	5,000 ANSI lumens	4,000 ANSI lumens	6,000 ANSI lumens	5,500 ANSI lumens	4,200 ANSI lumens	5,000 ANSI lumens
<b>Contrast Ratio</b>	3000 : 1 (using active IRIS)	3000 : 1 (using active IRIS)	3000 : 1 (using active IRIS)	3000 : 1 (using active IRIS)	3000 : 1 (using active IRIS)	3000 : 1 (using active IRIS)
<b>Throw Ratio (Distance : width)</b>	1.5 - 2.5 : 1	1.5 - 2.5 : 1	1.5 - 3.0 : 1 (with standard lens)	1.5 - 3.0 : 1 (with standard lens)	1.5 - 3.0 : 1 (with standard lens)	1.5 - 3.0 : 1 (with standard lens)
<b>Focus Distance</b>	34" - 596"	36" - 632"	37" - 1450" (with standard lens)	39" - 1537" (with standard lens)	38" - 1507" (with standard lens)	38" - 1507" (with standard lens)
<b>Display Size</b>	30" - 300"	30" - 300"	30" - 600"	30" - 600"	30" - 600"	30" - 600"
<b>Expected Lamp Life<sup>1</sup></b>	Approx. 3,000 hours (standard mode); 5,000 hours (Eco mode)	Approx. 3,000 hours (standard mode); 5,000 hours (Eco mode)	Approx. 2,500 hours (standard mode); 3,000 hours (Eco mode)	Approx. 2,500 hours (standard mode); 3,000 hours (Eco mode)	Approx. 2,500 hours (standard mode); 4,000 hours (Eco mode)	Approx. 2,500 hours (standard mode); 3,000 hours (Eco mode)
<b>Expected Filter Life<sup>2</sup></b>	Approx. 5,000 hours	Approx. 5,000 hours	Approx. 20,000 hours	Approx. 20,000 hours	Approx. 15,000 hours	Approx. 20,000 hours
<b>Speaker Output</b>	16W	16W	16W	16W	16W	16W
<b>Digital Input</b>	HDMI x 1 (HDCP compliant)	HDMI x 1 (HDCP compliant)	HDMI x 2 (HDCP compliant)	HDMI x 2 (HDCP compliant)	HDMI x 2 (HDCP compliant)	HDMI x 2 (HDCP compliant)
<b>Network (LAN) Wired</b>	RJ-45 port (10 base-T / 100 base-TX)	RJ-45 port (10 base-T / 100 base-TX)	RJ-45 port (10 base-T / 100 base-TX)	RJ-45 port (10 base-T / 100 base-TX)	RJ-45 port (10 base-T / 100 base-TX)	RJ-45 port (10 base-T / 100 base-TX)
<b>Network (LAN) Wireless</b>	USB-A, IEEE802.11 b/g/n - optional wireless adapter required	USB-A, IEEE802.11 b/g/n - optional wireless adapter required	USB-A, IEEE802.11 b/g/n - optional wireless adapter required	USB-A, IEEE802.11 b/g/n - optional wireless adapter required	USB-A, IEEE802.11 b/g/n - optional wireless adapter required	USB-A, IEEE802.11 b/g/n - optional wireless adapter required
<b>Weight</b>	Approx. 10.1 lbs.	Approx. 10.1 lbs.	Approx. 19.2 lbs.	Approx. 19.2 lbs.	Approx. 19.2 lbs.	Approx. 19.4 lbs.
<b>Supplied Accessories</b>	Remote control, power cord, computer cable, user's manuals, safety manual, lens cap, security label	Remote control, power cord, computer cable, user's manuals, safety manual, lens cap, security label	Remote control, power cord, computer cable, one standard ML703 lens, lens cover, user's manual, security label, application CD, adapter cover	Remote control, power cord, computer cable, one standard ML703 lens, lens cover, user's manual, security label, application CD, adapter cover	Remote control, power cord, computer cable, one standard ML703 lens, lens cover, user's manual, security label, application CD, adapter cover	Remote control, power cord, computer cable, one standard ML703 lens, lens cover, user's manual, security label, application CD, adapter cover
<b>Optional Accessories</b>	USBWL11N USB wireless adapter, MS-1 wired and MS-1WL wireless multifunction switchers, LCDS2000 soft sided case, HL02651 laser/wired remote control	USBWL11N USB wireless adapter, MS-1 wired and MS-1WL wireless multifunction switchers, LCDS2000 soft sided case, HL02651 laser/wired remote control	USBWL11N USB wireless adapter, MS-1 wired and MS-1WL wireless multifunction switchers <sup>3</sup>	USBWL11N USB wireless adapter, MS-1 wired and MS-1WL wireless multifunction switchers <sup>3</sup>	USBWL11N USB wireless adapter, MS-1 wired and MS-1WL wireless multifunction switchers <sup>3</sup>	USBWL11N USB wireless adapter, MS-1 wired and MS-1WL wireless multifunction switchers <sup>3</sup>
<b>Optional Lenses</b>	N/A	N/A	FL701, SL702, LL704, UL705	FL701, SL702, LL704, UL705	FL701, SL702, LL704, UL705	FL701, SL702, LL704, UL705
<b>Lamp</b>	CPX5021NLAMP (DT01171) with filter	CPX5021NLAMP (DT01171) with filter	DT01291	DT01291	DT01281	DT01291
<b>Remote Control</b>	HL02881	HL02881	HL02801	HL02801	HL02801	HL02801
<b>Filter</b>	MU07791	MU07791	UX38241	UX38241	MU06642	UX38241

<sup>1</sup> Actual lamp life will vary by individual lamp and based on environmental conditions, selected operating mode, user settings and usage. Hours of average lamp life specified are not guaranteed and do not constitute part of the product or lamp warranty. Lamp brightness decreases over time.

<sup>2</sup> Actual filter life will vary by individual filter and based on environmental conditions, selected operating mode, user settings and usage. Hours of average filter life specified are not guaranteed and do not constitute part of the product warranty.

<sup>3</sup> Switchers have limited function with this projector model

For sales information, please call  
**800.HITACHI**

For complete specifications visit  
**hitachi-america.us/projectors**

Visit our blog  
**dmd.hitachi-america.us/blog**



CP-HD9320, CP-X9110, CP-WX9210, CP-WU9410



CP-HD9321, CP-X9111, CP-WX9211, CP-WU9411



CP-X8170, CP-WX8265, CP-WU8460



CP-WU13K

**PROFESSIONAL**

	CP-HD9320/ CP-HD9321	CP-X8170	CP-X9110/ CP-X9111	CP-WX8265	CP-WX9210/ CP-WX9211	CP-WU8460	CP-WU9410/ CP-WU9411	CP-WU13K
<b>Projector Technology</b>	1 chip DLP technology	3LCD, 3 chip technology	1 chip DLP technology	3LCD, 3 chip technology	1 chip DLP technology	3LCD, 3 chip technology	1 chip DLP technology	3 chip DLP technology
<b>Resolution</b>	Full HD 1080p (1920 x 1080)	XGA 1024 x 768	XGA 1024 x 768	WXGA 1280 x 800	WXGA 1280 x 800	WUXGA 1920 x 1200	WUXGA 1920 x 1200	WUXGA 1920 x 1200
<b>White Light Output</b>	8,200 ANSI lumens	7,000 ANSI lumens	10,000 ANSI lumens	6,500 ANSI lumens	8,500 ANSI lumens	6,000 ANSI lumens	8,500 ANSI lumens	13,000 ANSI lumens
<b>Contrast Ratio</b>	2500 : 1 (using active IRIS)	3000 : 1 (using active IRIS)	2000 : 1 (using active IRIS)	3000 : 1 (using active IRIS)	2500 : 1 (using active IRIS)	3000 : 1 (using active IRIS)	2500 : 1 (using active IRIS)	2000 : 1
<b>Throw Ratio (Distance : width)</b>	Specification varies depending on lens	1.5 - 3.0 : 1 (with standard lens)	Specification varies depending on lens	1.5 - 3.0 : 1 (with standard lens)	Specification varies depending on lens	1.5 - 3.0 : 1 (with standard lens)	Specification varies depending on lens	Specification varies depending on lens
<b>Focus Distance</b>	71" - 1293" (with standard lens)	37" - 1450" (with standard lens)	68" - 1230" (with standard lens)	39" - 1537" (with standard lens)	73" - 1321" (with standard lens)	38" - 1507" (with standard lens)	69" - 1258" (with standard lens)	159" - 868" (with standard lens)
<b>Display Size</b>	50" - 600"	30" - 600"	50" - 600"	30" - 600"	50" - 600"	30" - 600"	50" - 600"	100" - 400" (with standard lens)
<b>Expected Lamp Life<sup>1</sup></b>	Approx. 2,000 hours (standard mode); 4,000 hours (Eco mode)	Approx. 2,000 hours (standard mode); 2,500 hours (Eco mode)	Approx. 2,000 hours (standard mode); 4,000 hours (Eco mode)	Approx. 2,000 hours (standard mode); 2,500 hours (Eco mode)	Approx. 2,000 hours (standard mode); 4,000 hours (Eco mode)	Approx. 2,000 hours (standard mode); 2,500 hours (Eco mode)	Approx. 2,000 hours (standard mode); 4,000 hours (Eco mode)	Approx. 2,000 hours (standard mode); 2,500 hours (Eco mode)
<b>Expected Filter Life<sup>2</sup></b>	Approx. 15,000 hours	Approx. 20,000 hours	Approx. 15,000 hours	Approx. 20,000 hours	Approx. 15,000 hours	Approx. 20,000 hours	Approx. 15,000 hours	Approx. 10,000 hours
<b>Speaker Output</b>	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
<b>Digital Input</b>	HDMI x 2 (HDCP compliant), DVI-D x 1, HDBaseT x 1, 3G SDI x 1	HDMI x 2 (HDCP compliant)	HDMI x 2 (HDCP compliant), DVI-D x 1, HDBaseT x 1	HDMI x 2 (HDCP compliant)	HDMI x 2 (HDCP compliant), DVI-D x 1, HDBaseT x 1	HDMI x 2 (HDCP compliant)	HDMI x 2 (HDCP compliant), DVI-D x 1, HDBaseT x 1	HDMI x 2 (HDCP compliant), Stereo DVI x 1, BNC x 1 (SDI/HDS/3G)
<b>Network (LAN) Wired</b>	RJ-45 port, (10 base-T / 100 base-TX)	RJ-45 port, (10 base-T / 100 base-TX)	RJ-45 port, (10 base-T / 100 base-TX)	RJ-45 port, (10 base-T / 100 base-TX)	RJ-45 port (10 base-T / 100 base-TX)	RJ-45 port (10 base-T / 100 base-TX)	RJ-45 port (10 base-T / 100 base-TX)	RJ-45 port (10 base-T / 100 base-TX)
<b>Network (LAN) Wireless</b>	USB-A, IEEE802.11 b/g/n - optional wireless adapter required	USB-A, IEEE802.11 b/g/n - optional wireless adapter required	USB-A, IEEE802.11 b/g/n - optional wireless adapter required	USB-A, IEEE802.11 b/g/n - optional wireless adapter required	USB-A, IEEE802.11 b/g/n - optional wireless adapter required	USB-A, IEEE802.11 b/g/n - optional wireless adapter required	USB-A, IEEE802.11 b/g/n - optional wireless adapter required	N/A
<b>Weight</b>	Approx. 36.6 lbs. (without lens)	Approx. 19.2 lbs.	Approx. 36.6 lbs. (without lens)	Approx. 19.4 lbs.	Approx. 36.6 lbs. (without lens)	Approx. 19.4 lbs.	Approx. 36.6 lbs. (without lens)	Approx. 74.9 lbs. (without lens)
<b>Supplied Accessories</b>	Remote control, power cord, computer cable, user's manual, security label, application CD, adapter cover	Remote control, power cord, computer cable, one standard ML703 lens, lens cover, user's manual, security label, application CD, adapter cover	Remote control, power cord, computer cable, user's manual, security label, application CD, adapter cover	Remote control, power cord, computer cable, one standard ML703 lens, lens cover, user's manual, security label, application CD, adapter cover	Remote control, power cord, computer cable, user's manual, security label, application CD, adapter cover	Remote control, power cord, computer cable, one standard ML703 lens, lens cover, user's manual, security label, application CD, adapter cover	Remote control, power cord, computer cable, user's manual, security label, application CD, adapter cover	Remote control, power cord, RS232C cable (cross, male to male), user's manual
<b>Optional Accessories</b>	USBWL11N USB wireless adapter	USBWL11N USB wireless adapter, MS-1 wired and MS-1WL wireless multifunction switchers	USBWL11N USB wireless adapter, MS-1 wired and MS-1WL wireless multifunction switchers	USBWL11N USB wireless adapter, MS-1 wired and MS-1WL wireless multifunction switchers	USBWL11N USB wireless adapter, MS-1 wired and MS-1WL wireless multifunction switchers	USBWL11N USB wireless adapter, MS-1 wired and MS-1WL wireless multifunction switchers	USBWL11N USB wireless adapter, MS-1 wired and MS-1WL wireless multifunction switchers	MS-1 wired and MS-1WL wireless multifunction switchers <sup>3</sup>
<b>Optional Lenses</b>	USL901, SL902, SD903W, ML904, LL905, UL906	FL701, SL702, LL704, UL705	USL901, SL902, SD903X, ML904, LL905, UL906	FL701, SL702, LL704, UL705	USL901, SL902, SD903W, ML904, LL905, UL906	FL701, SL702, LL704, UL705	USL901, SL902, SD903W, ML904, LL905, UL906	FLK01, FLK02, SLK03, MLK04, LLK05, ULK06
<b>Lamp</b>	DT01731	DT01471	DT01581	DT01471	DT01581	DT01471	DT01581	DT01591D
<b>Remote Control</b>	HL02804	HL02801	HL02803	HL02801	HL02803	HL02801	HL02803	HL03051
<b>Filter</b>	UX39551	UX38242	UX39551	UX38242	UX39551	UX38242	UX39551	MU08321 for front MU08331 for rear

<sup>1</sup> Actual lamp life will vary by individual lamp and based on environmental conditions, selected operating mode, user settings and usage. Hours of average lamp life specified are not guaranteed and do not constitute part of the product or lamp warranty. Lamp brightness decreases over time.  
<sup>2</sup> Actual filter life will vary by individual filter and based on environmental conditions, selected operating mode, user settings and usage. Hours of average filter life specified are not guaranteed and do not constitute part of the product warranty.  
<sup>3</sup> Switchers have limited function with this projector model

For sales information, please call  
**800.HITACHI**

For complete specifications visit  
**hitachi-america.us/projectors**

Visit our blog  
**dmd.hitachi-america.us/blog**